

3" Mobile Printer MX30i




Lightweight and portable
Provides for a Robust and Hasslefree Solution

Durable Lithium-Ion battery to decrease downtime

Compatible with labels or continuous paper

Drop in and print mechanism supports 1.5"~3" wide media

Larger roll capacity to support various applications



- Unique label detection supports various labels
- Supports various types of media with its easy Drop in and Print design



- Intuitive user panel:
- User friendly LCD screen
 - 4 status indication LEDs
 - 3 Function buttons: Power, Feed, Bluetooth



- High capacity batteries minimize downtime
- Compatible with labels or continuous paper
- 72 hour standby with up to 300 label cycles between charges
- Sleep mode standard



- Wired & wireless connectivity:
- Wired: RS232, USB ports
 - Wireless: Bluetooth, Wi-Fi

MX30i

Mobile Printer

Model		MX30i
Print Method		Direct Thermal
Resolution		203 dpi (8 dots/mm)
Print Speed		up to 4 IPS (101.6 mm/s)
Print Width		2.8" (72 mm)
Print Length		30" (~762 mm)
Processor		32 bit RISC CPU
Memory	Flash	128 MB Flash (60 MB for user storage)
	SDRAM	32 MB
Sensor Type		Gap sensor , Fixed transmissive sensor , Fixed reflective sensor
Media	Type	Direct Thermal receipt, anti-UV receipt, gap label, left side alignment
	Width	Inter-label gap size from 2 mm to 4 mm. 3 mm preferred
	Media roll diameter	Max. 3.15" (80 mm), Min. 1.5" (38.1 mm)
	Thickness	Max. 2.35" (60 mm) on 0.5" (12.5 mm) core Min 0.0508 mm, Max 0.165 mm
Printer Language		GPOS Emulations or EZPL / GZPL / GEPL Emulations
Software	Label design software	GoLabel (for EZPL only)
	Driver	MAC , Linux , Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1
	SDK	Win CE , .NET , Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 / Android
Resident Fonts	Bitmap fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A & B. 0°, 90°, 180°, 270° rotatable
	TTF fonts	CG Triumvirate™ (Bold / Italic / Underline). 0°, 90°, 180°, 270° rotatable
Download Fonts	TTF fonts	90°, 180°, 270° rotatable
	Asian Fonts	16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese (GB2312), Japanese (S-JIS), Korean (KS-X1001) 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
	Bitmap Fonts	Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
Barcodes	1-D Bar codes	Code 39, Code 93, EAN 8/13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13 digit, Japanese Postnet, I2 of 5 with human readable check digit, Standard 2 of 5, Industrial 2 of 5 , Logmars, Code 11, Code 49, Cadablock
	2-D Bar codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code
Code Pages		CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode UTF8, UTF16BE , UTF16LE
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from GoLabel
Interfaces		RS232+USB 2.0 port, mini-B type connector Bluetooth 2.1+EDR
Control Panel		4 dual color LEDs for Power, Battery, Communication, Error status indication. 3 buttons for Power, Feed and BT functions
LCD Display		Graphic OLED 128 x 64 dots with 3 buttons for Up, Down and Enter functions
Power Adapter		Switching power supply I/P: 100 / 240 V AC, 50 / 60 Hz, DC 9 V / 2.0 A
Battery		Rechargeable DC 7.4 V Li-ion battery, 2500 mAh or higher capacitance
Environment	Operation temperature	32°F to 122°F (0°C to 50°C)
	Storage temperature	-4°F to 140°F (-20°C to 60°C)
Humidity	Operation	10-90%, non-condensing
	Storage	10-90%, non-condensing
IP Rating		Intrusion Protection, IP42 requirement for case design, IP54 for protective case
Drop Level		1.5 meter height
Agency Approvals		CE EMC, FCC part 15B class B, FCC Part 15C, NCC, CB, UL, cUL, Energy Star V2.0
Dimension	Length	6.71" (170.63 mm)
	Height	3.11" (79 mm)
	Width	4.48" (114.01 mm)
Weight		1.47 lbs (670 g), with battery
Options		USB cable RS-232 cable Li-ion battery 4-bay battery charger station Car charger adapter Protective case WiFi (comply with IEEE 802.11b/g/n)

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.